

82 Rotation Film Oven For Asphalt



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Accuracy of Control:	163°C ± 1°C
Revolving speed of sample turntable:	5.5r/min
Time for each test:	5.25h
Dimensions of the workroom:	430 x 410 x 450mm
Mains voltage:	220V~2.5KW
Quantity of samples for each test:	4 Pcs



LYS-1.5

Asphalt Ductility Test Apparatus

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



Speed:	adjustable from 10mm $\pm$ 0.5mm/min to 50mm $\pm$ 2.5mm/min
Temp. Control:	25°C $\pm$ 0.5°C
Ductile length:	selectable 1.5m, 2m
Bath dimension:	1600 x 280 x 200mm (1.5m) 2100 x 280 x 200mm (2m)
Power supply:	220V 50Hz

LLC-15

Centrifugal Asphlath Extraction Apparatus



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Drum capacity:	>1.5L
Drum rotating speed:	$\geq 3000\text{r/min}$
Power:	400W

VGI

HCT-1

Bitumen High-speed Extraction Apparatus

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



Weight of material bowl:	3kg
Rated revolution :	3000rpm
Power Supply :	380VAC

LARGE HORIZONTAL AUTOCLAVE STERILIZER



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Model	WX-300L
Volume	300L
Voltage	220V, 50HZ
Power	2.5-4.5KW



Feature

1. Microcomputer control system, LCD dynamic display
2. Full automatic control for warming, sterilization and drying
3. Error analysis and failure warning displaying system
4. Overpressure auto-discharging at 0.2-0.22Mpa
5. Sterilization temperature 0-134°C can be set
6. Four shortcut keys for fixed sterilization programs: appliance, dressing, packing instrument, liquid
7. Safety and interlock device, quick opening structure
8. Two pressure gages indicating inner and interlayer pressure
9. Sterilization time and temperature can be controlled
10. All SUS304 stainless steel

Range of application

It's vertical autoclave sterilizer which is designed for the hospital, clinic, lab, etc. It's mostly suitable for sterilizing of surgical, dental instruments, glassware, culture medium and biological dressing, food and goods, etc.

LHB-II Asphalt Mixture Mixing Machine

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



Blending Cubage :	10L,20L
Temperature Range of Blend Bowl :	Room Temperature -200°C
Temperature Controlling Accuracy :	±2 °C
Stirring Blade Speed :	(1) Revolution Speed: 45RPM;
	(2) Rotation Speed: 75RPM;
Power :	220VAC,2000W,50Hz



SYD-0612

Asphalt Standard Viscometer



HOT!

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Circular water bath:	(1)Inner diameter :160mm;(2)Depth:116mm;
Sample tube :	4 pieces in 1 set;their diameters of offuse holes are $\phi 10\text{mm}\pm 0.025\text{mm}$, $\phi 5\text{mm}\pm 0.025\text{mm}$, $\phi 4\text{mm}\pm 0.025\text{mm}$,and $\phi 3\text{mm}\pm 0.025\text{mm}$ Respectively;
Ball-like stopper:	(1)Diameter of ball section; $12.7\pm 0.05\text{mm}$; Height of mark; $92\text{mm}\pm 0.25\text{mm}$; (2)Diameter off ball section; $6.35\text{mm}\pm 0.05\text{mm}$; Height of mark; $90.3\text{mm}\pm 0.25\text{mm}$;
Temperature controlling range:	Room temperature $\sim 90^{\circ}\text{C}$;
Temperature controlling Accuracy:	$\pm 0.1^{\circ}\text{C}$;
Timing resolution:	0.1 s,the maximum timing value 999,9 s;
Heating type:	By an electric heater heater;Use a circulation pump to circulate bath liquids,so that to control temperature of water bath; Heating power is 600 W;
Ambient temperature:	$-10\sim 35^{\circ}\text{C}$;
Relative humidity:	$\leq 85\%$;
Size:	Length 420mm,width 340,height 570mm;
Power supply:	AC 220V $\pm 10\%$,50Hz;
Total power consumption:	Not more than 700W;