

Sulphur tester

Product model : GMS3000

Product code : 04130647



Advantage :

- High-temperature adopt imported light-weight high quality heat preservation material, which has advantage of heat up quickly, good effect of energy-saving and good appearance;
- Adopting the device imported from American for hardware integration to avoid the error of software integration, which makes the result precise and reliable;
- Adopting integrated structure, integrating cracking furnace, electrolytic cell, mixer sample feeding motor, air purification systems and other components together.
- Using bolometric titration testing method that has the better speed than air shake gravimetric analysis method and high temperature combustion neutralization method, and ensures accurate measurement;
- The software accepts three-dimensional dynamic graphic interface, easy to operation and data automatically calculate, save and heating up quickly;
- Using a new type piston pump that has the advantages of small volume, low noise and long service life.

Parameter :

• Testing time :	3-6min/sample
• Sculpture testing range :	0.01%-20%
• Sample qty :	1pcs
• Precision of temperature controlling :	$\pm 3^{\circ}\text{C}$, special : $\pm 1^{\circ}\text{C}$
• Testing temperature :	Coal 1150°C , OIL 900°C or as requested
• Resolution :	0.001% , special : 0.0001%
• Power :	$\leq 4\text{KW}$
• Power supply :	(220 $\pm$ 22) VAC , (50 $\pm$ 1) Hz