

WASHING COLORFASTNESS TESTER(LARGER CAPACITY)



Containers

20 units of 550mL containers
20 units of 1200mL containers
Easy and Fast Setup

24 blank customer programs Gas
Spring Supporting Device Easier
Open More Safety



Touchscreen Control
32 testing programs built in

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

RF6018E



Product Information

Washing Colorfastness Tester may use for
determine the color fastness test of washing,
dyeing, drying clean and bleach detergent

Specification:

Specimen rack rotation speed	40± 2rpm
Temperature range	Room Temp. to 97°C
Temperature accuracy	±0.5°C
Rate of temperature rise	Max.2 °C/min
Internal materials	Stainless Steel 316L
Safety Device	Safety door switch over-temperature protector Low water level protection
Automatic Water Inlet and Draining	

Test Standards

AATCC 28/61/132/151/190 BS 1006 C01-C05 ISO 105 Part C01-
M&S C4/C5/C10A/P3B FTMS 191-5610 C06/C08/D01
GB/T 5711/3921 NEXT TM2/3/5

Ordering Information

RF6018E Washing Colorfastness Tester (Small capacity)
RF6018E/1 550mL container (with gasket 2 piece)
RF6018E/2 1200mL container (with gasket 2 piece)
RF6018E/3 Stainless Steel Ball (100 piece/pack)
RF6018E/4 Stainless Steel Disc (25 piece/pack)
RF6018E/5 550mL Container's Gasket (8piece/pack)
RF6018E/6 1200mL Container's Gasket (8piece/pack)
RF6018E/7 Rubber Ball (Dia. 9.5mm) (100pcs/pack)



Specimen Container



Rubber Ball



Stainless Steel Disc



Teflon Sheet