

AUTOMATIC GRANULE PACKING MACHINE

HL-K200

FEATURES:

Three - step sealing roller, four side sealing. Film runs continuously fast and efficient as well as stable in faction, low noise,firm air tight sealing, reliable in air tight, smooth and delicacy in bag's outlook, and extra ordinary in packing efficiency. Famed PLC and touch screen are adopted to make adjusting easy. Photoelectric tracking system is adopted to ensure correct printing and accurate counting. Famed transducer is adopted for step less adjust running speed, intelligent temperature controller use to adjust sealing temperature with reliable performed and convenient to adjust. Servo motor driver is adopted , pouch length can be set up directly at the touch screen, at the same time longitudinal sealing and trans verse sealing be able to auto in-phase tracking, it saves more time and material compare with mechanical driver, and bag pulling more smooth and more easier to adjust. measuring cup is adopted for automatic feeding and precise in dosing it can fill material with high temperature, more suitable to high speed bag packing machine's using. Applicable to a wide range of use . Cutting method option: flat cutting (with tear notch), fracture line cutting.

USAGE:

Suitable for packing loose, non sticky granular material such as pellets, sugar, salt, soup, outmeal,seeds,coffee, instant drink, pills and much more. Most commonly used in the pharmacy, food, daily chemicals and algucul tue industries.



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

SPECIFICATION

Pouch length	40-200 mm	Adjustable (coming within the length)
Pouch width	50-175 mm	Should change bag former
Filling capacity	1-150ml	Based on dosing system
Packing speed	50-150bags/min Single lane	Based on material and bag size
Feeding device	Measuring cup	
Standard cutting device	smooth cutting, with tear notch, dashed line cutting	
Sealing type	4 side sealing	A choice between two
Driver system	Servo motor /step motor	
Applicable film	PET/AL/PE, PET/PE, NY/PE, NY/AL/PE etc.	
Film width	350mm	
Film roller specification	Film outer diameter<300mm, film inner diameter 70-76mm	
Voltage	220V single phase, 50Hz	Made in accordance with customer request
Total power	5.5	
G.W	650Kg	
Package dimension	1400 X 1000 X 2100mm (L X W X H)	
Optional device	Ink roller printer, Embossing type dating unit	