

贴标机系列 Labeling Machine Series

JTL-1860 不干胶双面贴标机

Automatic Adhesive Double Sides Labeling Machine

产品简介:

自动不干胶贴标机主要用于食品、制药、日化、农药、化工行业的不规则或规则产品，对应同时贴附侧面两张标签或单面贴标均可。全机采用304不锈钢和铝合金制造，贴标头使用进口步进电机或伺服电机驱动，电眼选用进口高级光电，PLC配合大型人机界面控制，并具备自动输送、自动分瓶、自动导正，光电检瓶、送标、贴标准确，生产速度快等特点。校整机构确保瓶形贴标时的同线与对中性、压顶装置伸缩缓压功能，解决了瓶形高低给贴标时带来的误差，高速运转中稳定性更好。广泛适用于医药、化工、日化、食品、油脂、农药等行业。

可选配：圆瓶周贴装置、定位装置实现一机多用功能的贴标要求。可选配套：自动送料/自动收集/热烫打码或喷码等。系统选配：透明标签检测、条码阅读器、对产品在线检测，二维码打印及扫描。

Introduction:

Automatic self-adhesive labeling machine is mainly used in food, pharmacy, daily chemicals, pesticide, chemical industry, oil products, can stick two-side label and one side label, whole machine use SS304 and aluminum alloy. Labeling head use stepping motor or servo motor drive, electric eye choose Japan advanced photoelectric, use PLC programmable control and has automatic conveying, automatic bottle separating, automatic bottle guiding, photo electricity detection bottle, label-sending, labeling accurate and speed fast. The adjust structure assures the accuracy when labeling different size of bottles, keeping stable when the machine is running with high speed.

Chosed parts: Round bottles winding and sticking device and the positioning device meet the requirements of one machine with multiple functions.

Supporting parts: Bottle feeding plate, collecting system, hot stamping machine, ink jet printing machine.

System can be choosed: code testing, reading machine, online testing, two microcode printing and scanning.



豪华伺服型 Servo type↓



步进型 Step type↓



Note:

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

主要技术参数 main technical parameter

1、贴标速度/Labeling speed	0-25米/分 (meter/m)
2、贴标物高度/Object height	30-280mm
3、贴标物直径/ Object diameter	20-200mm
4、标签高度/ Label height	≤150mm
5、标签长度/Label length	25-300mm
6、贴标精度/ Labeling error	±1mm
7、纸卷内径/Roller inner dia	Φ76mm
8、纸卷外径/ Roller outer dia	Φ350mm
9、整机功率/Power	1.2KW
10、电源/ Power supply	220V/50Hz
11、机器尺寸/Dimension	2800×1450×1360mm
12、重量/Weight	300Kg