

Mesin Labeling Botol Model : Vertical



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

Electrical Configuration	No.	Name	Brand
	1	Switch	Schneider (waterproof)
	2	Curent Protector	Schneider (waterproof)
	3	Electroma gnetic contacto	Schneider (waterproof)
	4	Relay	Omron
	5	Button	Schneider (lighting)
	6	Photoelectric sensor	German sick
	7	Invester	Panasonic
	8	PLC	Panasonic
	9	Motor	KINCO
	10	Bearing	NSK
	11	Interface	EASYVIEW
	12	Machine's body	SUS304 stainless steel

Component Parts	No.	Name Of the mechanical sructure	Totle
	1	label unwid	One Set
	2	Bottle hugger system	One Set
	3	Feeding device	One Set
	4	Fork Photo Sensor	One Set
	5	Mandrel	One Set
	6	Shrink Tunnel	One Set
	7	Conveyor 7.32m	One Set
	8	Driving Section	One Set
	9	Adjustable Knife Plate	One Set
	10	Label brushing	One Set
	11	Auto up/Down Table	One Set
	12	Interface Control unit	One Set
	13	Brush Section	One Set
	14	Protection hood	One Set

Technical Parameters	SLM-150 Auto shrinkable label inserting machine	
	Main machine	1000mm L* 860 mm W * 1800 mm H
	Weight	Approximately 500kgs
	Diameter of bottle	ψ25- ψ50m/m, ψ50- ψ95m/m, ψ95- ψ125m/m, one dimension to be chose from three options, special, specification can be made to meet customer's demands.
	Shrinks label cut lenght	25mm – 250mm
	Label thickness	0.035 mm-0.08 mm (PVC,PET,OPS)
	Inner core	5" – 10"
	Machines's speed	9000BP/H(after filling,shrinlabel,cut lenght 100mm)
	Voltage	3- PHASE 220V/380V
	Power	15KW(main machine : 3KW, power shrink tunnel : 12KW