

LWT-2 SERIES TABLEWARE APPLICATOR



LWT-2 series Tableware Applicator :

JLWT-2 series tableware applicator is used to paste straw, spoon, fork and other utensils on the outer surface of package. LWT-2 series tableware applicator was developed from LWT-1. In order to enhance the speed and stability, LWT-2 has been designed by leaps and bounds. LWT-2 is almost double capacity which means the maximum speed is up to 15,000 packs/hour, and with the same performance and easy to maintain which makes LWT-2 very good at cost-effectiveness. This has been accepted and proved by Mengniu, Hekuierkang, Fuquan Dairy and Xiaguang and so on.

There are LWTIP-2, LWTEL-2, LWTKM-2, LWTSG-2 accordingly in LWT-2 series which are used for IPI, Ecolean, Combibloc and Sikok production lines.

Technical Parameter

Dimension	: 1230mm (L) X 890mm (W) X 1700mm (H)
Power supply	: 220V AC/50Hz
Power	: 5.5Kw
Instrument air	: 0.7 MPa (7bar)
Normal speed	: 10,000 packs/hour
Maximum speed	: 15,000 packs/hour

Following items need to be specified while ordering :

- Straight or bent straws used;**
- The direction of outgoing packages from filler;**
- Option for straw detecting system which is used to detect whether straw is applied for each package, otherwise, the package will be pushed out of the conveyor.**