



MAIN TECHNICAL PARAMETERS :

Model	GD6-300C	GD6-250C	GD6-200C
Working position	Six working position		
Pouch material	Laminated film\PP\PE etc.		
Pouch pattern	Stand-up pouch ,flat		
Pouch size	W:200-300mm L:200-450mm	W:150-260mm L:150-350mm	W:100-210mm L:100-350mm
Speed	8-30bag/min	8-35bag/min	10-60bag/min
Weight	1300KGS	1200KGS	1000KGS
Voltage	380V 3phase 50HZ/60HZ		
Total power	3.5KW	3.5KW	2.5KW
Air Compressor	0.6m ³ /min (Provided by user)		

YJL-500A Liquid & Paste Filler

- 1、 it can apply in: measure liquid and catsup like syrup, redeye, peanut butter, scour and so on.
- 2、 This machine is semiautomatic piston style liquid canning machine.
- 3、 The design of the machine is in reason with artful model , and it is convenient to handle.
- 4、 The part where touch to the material is made of stainless steel is accord with the request of GMP.
- 5、 The filling quantity and speed can be adjusted, it is accurate.
- 6、 The canning cobbra of the machine use the setting of defending leak and draw bench.

Product process

- 1、 Giving bag
- 2、 Coding date
- 3、 Open bag 1st ((thickness of bottom ≥ 1mm stand-up bag)
- 4、 Open bag 2nd
- 5、 Filling
- 6、 Sealing 1st
- 7、 Sealing 2nd
- 8、 Forming & output packages

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Specifications

Model	GD6-200A+YJL-500A
Working position	Six-working position (Optional : Eight)
Pouch material	Laminated film
Pouch pattern	With spout pouches, pouches, flat bags (side sealing, four sides sealing, bag, zipper bag)
Scope packaging	10-500ml (By replacing the charging head) (Optional >500ml)
Pouch size	W:100-210mm L:100-350mm
Speed	≤35pouches/min(The speed depends on the product status and filling weight)
Weight	1400KGS
Voltage	380V-3PHASE 50HZ/60HZ
Total power	3.5 kW
Air Compressor	0.6m ³ /min(supply by user)