

AUTOMATIC POWDER PACKING MACHINE

HL - F200

FEATURES:

1. Two step roller for side sealing, continuous running not only fast in speed stable in running, low in noise but also firm in sealing, reliable in airtight with bags coming smoothly and fine, high in packing efficiency.
2. An imported frequency changer is adopted for step-less speed adjusting, intelligent temperature at the sealing. It has reliable performance, convenient operation.
3. Photoelectric tracking system is adopted to ensure the automatic correcting of the double face printing design on packing bags, precise in counting.
4. An imported transducer is adopted to make adjusting easy. Intelligent temperature controller regulates sealing making it even more convenient.
5. Step motor/servo motor driver is adopted, pouch length can be set up directly at the touching screen, at the same time longitudinal sealing and transverse sealing be able to auto in -phase tracking, it saves more time and material compare to mechanical driver, and with bag pilling more smooth and even easier to adjust.
6. Screw type feeding system is adopted, precise in measuring, can fill material at high temperature, more suitable to high speed bag packing machine's using
7. Applicable to a wide range of use. Cutting method can choose flat cutting or fracture line cutting, and can match with link coding machine.

USAGE:

Suitable for packing loose, non sticky powder material such as bean powder, drug powder and much more. Most commonly used in the pharmacy, food, dairy, and agriculture industries.



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

SPECIFICATION

Pouch length	40-200mm (adjustble)
Pouch width	50-200mm (should change bag former)
Max packing speed	50-120bags/mm (depend on punch size and material)
Filling capacity	2-150ml /bag
Applicable film	PET/AL/PE PET/PE NY/AL/PE NY/PE/aluminize/complex film
Max film width	350mm
Max film diameter	Φ300 mm
Film core diameter	Φ70-76 mm
Electric source	220V single phase 50Hz (do as customer 's request)
Total power	5.5kW
G.W	650Kg
Package size	1800*1000*2200(L x Wx H)