

Horizontal Bag Packing Machine

产品简介:

本机采用国际先进技术，可用于三边和四边封铝膜袋袋装产品。机器采用微电脑PLC可编程控制，光电传感，采用伺服电机下料。填充方式灵活，对粉剂、水剂、粘稠体及微颗粒物等不同剂型产品选用不同的填充方式。本机包装速度快，计量范围大，性能稳定，操作方便，外型美观平整。

Introduction:

The machine using the international advanced technology and can be used for the trilateral and four edge-sealing aluminium film bag packaged products. Machine using the adopts microcomputer PLC programmable control, photoelectric sensor, using the servo motor, filling way is flexible, and micro particles of powder, water and dope different dosage forms, such as product to choose different way of filling. This machine packing speed, wide measuring range, stable performance, convenient operation, good appearance is flat and level.



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!



主要技术参数 main technical parameter

1、生产速度/Production speed	30-50袋/分钟 (bag/min)
2、包装容量/Filling volume	50g
3、计量精度/ Measurement precision	±1.5%
4、包装袋最大尺寸/ Maximum bag size	110(W)×130(H)mm
5、包装袋最小尺寸/Minimum bag size	50(W)×50(H)mm
6、包装卷膜最大直径/ Maximum film-roll diameter	500mm
7、包装膜卷孔留内径/Roll's interior diameter	70-80mm
8、总功率/Total Power	3KW
9、电源电压/ Voltage	AC380V/50Hz
10、机器尺寸/Dimension	2150×750×2200mm
11、重量/Weight	750Kg