



Full automatic standing pouch bag Filling & Packing Machine



Applications :

All kinds of grains, powder, solids, granule, liquid etc, such as: candy, nuts, raisins, peanuts, soup, liquid paste (sauce), food Ingredients powder, nuts, Rice granule, potato chips, chocolate, biscuits, cement powder, agriculture fertilizer, chemical powder, and so on.

Safety and Hygiene:

- No pouch/ incorrect pouch opening-no fill-no seal, machine alarm. Machine alarm and stop when the inadequate air pressure.
- Safety guards with safety-switches, machine alarm and stop when the safety guards are Hygienic construction, the product contact parts are adopted sus304 stainless steel.
- Imported engineering plastic bearings, no need to oil, no contamination.
- Oil-free vacuum pump, avoid the pollution of the production environmental.

Note :
Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

Main Feature And Characteristics

A Wide Range of Pouches	All kinds of pre-made pouches
High Speed Capacity	10~20bags/min (according weight, product feature)
Filling Volume	2,5kg / 4kg / 5kg & 10kg (according to costumer requested)
Easy to Operate	PLC controller and color touch screen, fault indicator on the touch screen
Easy to Adjust	Only about 10 minutes to change different pouches
Frequency Control	Speed can be adjusted by frequency conversion within the range.
High Automation System	Full automatic in weighing and packing process, Machine will trigger the alarm automatically when failure.

Technical parameters :

Bag Material	PP Woven Bag? Laminated film (Including aluminium foil film), PP, PE, etc
Bag Shape	Zipper Bag, Stand up Bag, Flat Bag, Four Side Sealing, Gusset Bag, etc
Bag Size	Width : 240~350mm Length : 250~600mm
Speed	10~20bags/min (depend on the product weight and bag shape)
Filling Volume	2,5kg / 4kg / 5kg & 10kg (according to costumer requested)
Main Machine Weight	1200 Kgs
Voltage	380V / 3 Phase / 50Hz
Main Power	2,5 kW
Compressed air needed	0,6m ³ /min