

RUBBER-PLASTIC KNEADING MACHINE

X (S) N- Series



Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

TECHNICAL DATA

项目Item	型号Model	X(S)N-3X32	X(S)N-10X32	X(S)N-20X32	X(S)N-35X30	X(S)N-55X30	X(S)N-75X30	X(S)N-110X30	X(S)N-150X30
捏炼总容积 Total Volume of kneading chamber	L	8	25	45	75	125	180	250	325
密炼总容积 Total Volume of mixing chamber	L	3	10	20	35	55	75	110	150
主驱动电机功率 Driving motor power	KW	5.5	15	30	55	75	110	185	220
翻转电机功率 Tipping motor power	KW	0.55	1.1	1.5	2.2	3.0	4.0	5.5	5.5
翻转角度 Tipping Angle		135	140°	140°	140°	140°	140°	140°	140°
转子轴转速 (前/后)(front/back) Rotational speed of the rotor	r/min	0-60,32/24.5	30/23.5	30/25	30/24.5	30/24.5	30/24.5	30/24.5	30/24.5
压缩空气工作压力 Flow rate of compressed air	Mpa	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8	0.6-0.8	0.6-0.8	0.6-0.8	0.6-0.8
压缩空气流量 Flow rate of compressed air	m3/min	≥0.3	≥0.5	≥0.7	≥0.9	≥1.0	≥1.0	≥1.5	≥1.5
冷却水压力 (炼胶) (rubber mixing) Pressure of Cooling water	Mpa	0.2-0.4	0.2-0.4	0.2-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4
加热蒸汽压力 (炼塑) (Plastication) Pressure of heated steam	Mpa	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8	0.5-0.8
外形尺寸 Overall dimensions(LXWXH)	MM	1660X960X1750	2580X1300X2280	2630X1520X2550	3200X1900X2945	3360X1950X3050	3760X2143X3135	4075X2712X3580	4200X3200X4000
重量 Weight	kg	2000	3300	4500	6500	7200	10000	14500	19500