

VGI



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!


STRUCTURE CHARACTERS :

1. The roll is made temperature of the chilled cast iron of vanadium and titanium alloy, so the surface is hard and wearable;the internal processing can make the temperature of the roll surface well-proportioned.
2. This machine has overload protection devices, and the major components cannot be damaged because of over loading.
3. This machine is equipped with emergency braking device. When an emergent accident happens, draw the pull rod, and then the machine will stop at once. It is safe and reliable.
4. he transmission system adopts either hard tooth flank dual axis reducer or NGW hard tooth flank planet reducer, which hascompact structure, low noise and high efficiency.
5. The base of the machine is a complete frame, so it's very convenient for for instalation.

Main Technical Parameters :

Item		Model	WTO XK-160	WTO XK-250	WTO XK-360	WTO XK-400	WTO XK-450
Roll Diameter	mm		160	250	360	400	450
Roll Working Length	mm		320	620	900	1000	1200
Front Roll Linear Speed	r/min		9	16.3	16.7	19.3	21.8
Speed Ratio Of Rolls			1:1.35	1:1.1	1:1.25	1:1.27	1:1.27
Max Roll Space	mm		4.5	8	10	10	12
Compound feeding Capacity	Kg		1-2	10-15	20-25	18-35	50
Motor Power (380Volt - 50Hz)	Kw		5.5	18.5	30	45	55
Dimension	L	mm	1133	2722	3820	4240	4875
	W	mm	920	1115	1530	1780	1840
	H	mm	1394	1345	1700	1760	1830
Gross Weight	Ton		~2	~3.2	~6.5	~8	~11.4

OPEN MIXING MILL



Drilled roll



Corrugated roll



Smooth roll



Final Products