

# Mesin Open Mixing Mill



| Model                                        | RT-110B-1                      | RT-110B-2                      |
|----------------------------------------------|--------------------------------|--------------------------------|
| Roller Diameter (metric/inch)                | 120mm/4in                      | 160mm/6in                      |
| Roller Face Width                            | 320mm                          | 320mm                          |
| Mixing Capacity                              | 0.3~2kg                        | 0.5~3kg                        |
| Picking Device                               | SUS304 Stainless steel hopper  | SUS304 Stainless steel hopper  |
| Roller Temperature                           | RT~water temperature           | RT~water temperature           |
| Heating Method                               | Water-cooled cooling           | Water-cooled cooling           |
| Temp Accuracy                                | ±3C                            | ±3C                            |
| Temperature Controller                       | PID control                    | PID control                    |
| Roller Rev                                   | frequency control              | frequency control              |
| Roller Ratio Adjusted According Requirements | 1:1.22/1:1.35<br>1:1.4         | 1:1.22/1:1.35<br>1:1.4         |
| Roller Hardness                              | 50~60HRC                       | 50~60HRC                       |
| Roller Processing                            | Mirror polishing chrome plated | Mirror polishing chrome plated |
| Roller Spacing                               | 0.1~8mm adjustable             | 0.1~8mm adjustable             |
| Spacing Display Mode                         | Calibration/digital display    | Calibration/digital display    |
| Safety Device                                | Collision type emergency stop  | Collision type emergency stop  |
| Safety Device Number                         | 7 PCS                          | 7 PCS                          |
| Special Function                             | Emergency stop inversion       | Emergency stop inversion       |
| Motor Power                                  | 4.5KW                          | 5.5KW                          |
| Power Voltage                                | 3phase,AC380V                  | 3phase,AC380V                  |
| Dimension                                    | 1x1.1x1.4(M)                   | 1x1.1x1.5(M)                   |
| Weight                                       | About 2T                       | About 2.5T                     |

**Note :**

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!