



GHZD Vacuum Hot Press



FUNCTION AND ASSEMBLE PARTS

1. Multi -functional machine applicable for two-layer or three-layer molds
2. Fast mold open/close for high production efficiency, and slow clamp for mold protection
3. Automstic mold forward/backward and two layer ejector for lower labour intensity.
4. Equipped with two pumps and two oil circuits with low noise, synchronous operation of two tables realizable;
5. pic-controlled electrical system for easy operation.
6. Optional plate turn over mechanism which is more applicable for the processing of such products as valve and nipples.
7. Vacuumizing shortens cure time to improve quqlity and output.
8. Partial hydraulic components are genuine products from germany, america and taiwan.



MAIN TECHNICAL PARAMETER

Project	Unit	Model		
		GHZD-200T	GHZD-250T	GHZD-300T
Clamping force	T	200	250	300
Stroke	mm	300	300	300
Dimension of working table	mm	500x500	600x600	650x650
Power of main machine	kw	11	11	11
Opening type		Forward-ejector		
Heating power of dual-axis	kw	25.6	36	42
Total power	kw	36.6	47	53
Weight	T	11.4	12.3	13.8
Overall dimension	mm	3250x3500x2600	3300x3500x2600	3500x3700x2600

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!