

HYZ-***Y 系列橡胶注压成型机
Y series rubber transfer press

Y

The models

HYZ-***J

Transfer press structure
Rating clamping force

Pump Machine

supplier code

HYZ - 200Y



MACHINE FEATURES:

Adopt four column structure ensure machine durability , oil tank, power cabinet , monitor on the right, reserve the back side for operation, suitable and economical for all kinds of rubber products.



Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Y SERIES

MAIN TECHNICAL PARAMETERS

Model	HYZ - 50Y	HYZ - 750Y	HYZ - 100Y		HYZ - 200Y		HYZ - 300Y		HYZ - 400Y	HYZ - 500Y
Injection volume (cm³)	500	1000	2000	3000	3000	4000	3000	4000	10000	10000
Clamping force (KN)	500	750	1000		2000		3000		4000	5000
Platen size (mm)	400 x 400	400 x 600	550 x 550		550 x 550		600 X 700		800 x 900	630 X 1600
Dimension Btwn Tiebar (mm)			585 x 335		650 x 360		710 X 510		990 x 570	780 X 560
Space of platens (mm)	500	650	500		570		750		780	940
Max. clamping stroke (mm)	300	350	450		500		600		570	700
Min. mold thicknes (mm)	210	310	60		80		160		220	250
Heating power (KW)	8	12	12		12		18		26	36
Total power (KW)	22	25	25		28		40		46	60
Machine dimension L x W x H (m)	18 x 1.2 x 2.9	2.1 x 1.3 x 3.5	2.5 x 1.2 x 3.8		2.5 x 1.7 x 4		3 X 2 X 4.2		2.9 x 2.8 x 5.6	3.5 X 2 X 5.8
Machine weight (Ton)	2.5	3	4.8		6		9		13	16