

HYZ- 200E

**MACHINE FEATURES:**

Four- column, oil tank, power cabinet and display screen right operation equipped with HTV stuffing (option) Suitable for producing insulator arrester, brushing, cable joint and all kinds of mold products.

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

E SERIES MAIN TECHNICAL PARAMETERS

Model	HYZ-50E		HYZ-100E		HYZ-150E		HYZ-200E		HYZ-300E		HYZ-400E		HYZ-500E		HYZ-600E	
Injection volume (cm ³)	300	500	500	100	1000	2000	1000	2000	2000	3000	3000	4000	3000	4000	5000	6000
Clamping force (KN)	500		1000		1500		200		3000		4000		5000		6000	
Platen size (mm)	400x400		500x500		550x550		550x550		600x700		700x700		700x700		800x900	
Dimension Btwn Tiebar (mm)	540x290		610x335		585x335		650x360		710x510		860x490		770x550		980x550	
Space of Platens (mm)	400		500		570		570		750		710		750		800	
Max. Clamping stroke (mm)	350		450		500		500		600		500		700		700	
Min. Mold thickness (mm)	60		60		80		80		160		220		60		110	
Nozzle diameter (mm)	Φ5		Φ5		Φ5.5		Φ5.5		Φ5.5		Φ5.5		Φ6		Φ8	
Arc Radius of Nozzle (mm)	SR15		SR19		SR19		SR19		SR19		SR19		SR19		SR19	
Heating power (KW)	8		12		12		12		18		21		26		30	
Total Power	22		25		28		28		40		45		55		60	
Machine (KW) Dimension L x W x H (m)	1.05x1.6x2.9		3.3x1.6x3.3		3.5x1.8x3.9		3.5x1.8x3.9		3.8x2x4.5		4.2x2x4.5		3x2x4.6		4x2.5x5	
Machine weight (Ton)	2.5		5.5		7.5		8		10		12		15		23	