



F HYZ-F Series Rubber Injection Molding Machine

HYZ- 250F



MACHINE FEATURES:

The large type machine adopt horizontal quadrangle clamping structure moving smoothly. Equipped with super-large injection capacity device and specific pump for LSR, suitable for bushing, arrester, in sulator, the small type machine adopt horizontal for column clamping structure, suitable for producing cable joint and kinds of product with LSR.

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

F SERIES MAIN TECHNICAL PARAMETERS

Model	HYZ-50F	HYZ-75F	HYZ-100F	HYZ-150F	HYZ-200F	HYZ-250F	HYZ-400F
Injection Volume (cm³)	3000	3000	4000	5000	10000	130000	130000
Clamping force (KN)	500	750	1000	1500	2000	2500	4000
Platen size (mm)	450x650	700x700	700x1000	700x1200	800x1600	1250x2600	1500x3000
Dimension Btwn Tiebar (mm)							
Space of Platens (mm)	750	850	1000	1200	1600	2400	2700
Max. clamping stroke (mm)	650	650	800	900	1300	2000	2000
Min. mold thickness	110	110	210	310	310	410	710
Heating power (KW)	10	18	26	30	46	118	160
Total power (KW)	22	15	28	28	40	45	55
Machine Dimension LxWxH (m)	2.2x1.1x1.6	2.5x1.2x1.8	2.8x1.4x2	3x1.6x2.1	3.3x1.8x2.2	4.8x3x3.2	5.6x3x4.5
Machine weight (Ton)	25	3	5	7	9	20	35