

Four-cylinder Flat Vulcanizer

Push-pull

XLB-D (Y) 1500x1500x1/4.00MN
 XLB-D (Y) 1600x1600x1/6.30MN
 XLB-D (Y) 2000x1400x1/5.00MN
 XLB-D(Y) 3000x3000x1/33.00MN

(FRAME)
 (FRAME)
 (FRAME)
 (FRAME)

Technical Data

Type	XLB-D (Y) 1500x1500x1	XLB-D (Y) 1600x1600x1	XLB-D (Y) 2000x2000x1
Nominal Molding Power (MN)	4.00	6.3	12.00
Working Layer Number	1	1	1
Piston Stroke (mm)	250-800	250-800	250-800
Main Motor Power (KW)	18.5	18.5	18.5
Plate Clearance (mm)	250-800	250-800	250-800
Calefaction Manner	Steam Ecetrictity	Steam Ecetrictity	Steam Ecetrictity
Electric Pipe Heating Power	4-Ø100	4-Ø360	4Ø-500

Note :
 Due to keeping innovation,
 the specification and
 Machine pictures or color
 are subject to alteration
 without notice!

Feature

There is four-cylinder flat vulcanzier. This Machine is generally adopted frame type with our-cylinder, and it mainly used to produce various ubber products, such as solid tire, shoe sole, rubber tile, etc.

