



# Frame Flat Vulcanizer

XLB-D(Y) 1400\*600\*1/2.5MN ( 框架式 Frame)  
XLB-D(Y) 2000\*1000\*1/6.00MN ( 框架式 Frame)  
XLB-D(Y)2500\*1000\*1/10.00MN ( 框架式 Frame)

## Technical Data

| Type                               | XLB-D ( Y ) 700*700*1/2     | XLB-D ( Y ) 800*800*1/2     | XLB-D ( Y ) 1000*1000*1/2   |
|------------------------------------|-----------------------------|-----------------------------|-----------------------------|
| Nominal molding power ( MN )       | 1.00                        | 1.00/1.60                   | 1.00/1.60                   |
| Working layer number               | 1-2                         | 1-2                         | 1-2                         |
| Piston stroke ( mm )               | 250-500                     | 250-500                     | 250-500                     |
| Main motor power ( KW )            | 2.2                         | 2.2                         | 2.2                         |
| Configuration ( mm )               | 125-500                     | 125-500                     | 125-500                     |
| Calefaction manner                 | 电、( 油 ) 汽 Steam ecectricity | 电、( 油 ) 汽 Steam ecectricity | 电、( 油 ) 汽 Steam ecectricity |
| Plate clearance                    | 框架式 Frame                   | 框架式 Frame                   | 框架式 Frame                   |
| Electric pipe heating power ( KW ) | 42                          | 48                          | 80                          |

**Note :**  
Due to keeping innovation,  
the specification and  
Machine pictures or color  
are subject to alteration  
without notice!

## Feature

There is frame flat vulcanizer. This machine is generally adopted frame type, and it mainly used to produce various rubber products, such as solid tire, shoe sole, rubber tile, etc.

