

MODEL

TYM-W3535

注：Assuming the LSR density: 1.2g/cm³

注射装置 INJECTON UNIT

射胶筒直径 THE DIAMETER OF INJECTION PAIL	mm	30
射胶筒有效长度 THE LENGTH OF INJECTION PAIL	mm	150
理论注射容量 SHOT VOLUME(THEORETICAL)	ml	120
注射速度 INJECTION RATE	ml/s	25
注射压力 INJECTION PRESSURE	t	12.5
射嘴圆球半径 Nozzle Radius	mm	R19

锁模装置 CLAMPING UNIT

锁模力 CLAMP FORCE	t	95
移模行程 OPENING STROKE	mm	400
模柱间距 THE SPACE BETWEEN TIE-BARS	mm	350×350
最小模板间距 MIN. MOLDBOARD DISTANCE	mm	100
顶出行程 EJECTOR STROKE	mm	100
顶出力 EJECTION FORCE	t	7.8

其它 OTHERS

油泵压力 PUMP PRESSURE	Mpa	25
油泵马达功率 PUMP MOTOR POWER	kw	7.5
电热功率 HEATING POWER	kw	9
外型尺寸(长×宽×高) MACHINE DIMENSION(L×W×H)	mm	4600×1200×1800 (including the dosing unit)
模具定位圈直径 MOULD ORIENTATION RING DIAMETER	mm	Φ100
送料机规格 THE SPECIFICATION OF THE DOSING UNIT	kg	200kg/20kg

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!