

MESIN PENEMPELAN KEMBANG VULKANISIR



	for 15"-22.5"
	1500X1200X2000 mm
Description Dimension (P X L X T)	• Pressure the tread on the surface of old tyre, and put the air out among the tread and cushion gum and tyre surface. • The thread pitch of pinch roller screw mandrel control the speed and pressure, make the pinch roller roll from the middle to both side. • Optional expansion rim : 15"-16", 17.5"-19.5", 20"-22.5", 20"-22.5" (width:250mm), 20"-22.5" (width:300mm), 20"-22.5" (width:350mm), 24" and welcome special size order.
Function	• Standard layout : 15"-16", 20"-22.5" expansion rim and tread cutting machine. • Optional function : control system of pre tightening force on the tread, automatic tread centration system, infrared ray tread centration system • Average tire building time: 5 mins.

MESIN PEMARUT (BUFFING)



Note :
Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

	for 15"-22.5"
	1800 x 1700 x 1500mm
Description Dimension (P X L X T)	• Polishing the old pattern rubber to meet the needs of tire vulcanization • Radius of radian range is 400 ~ 800mm, also polish the appointed radian • Optional expansion rim: 15"-16", 17.5"-19.5", 20"-22.5", 20" - 22.5" (width:250mm), 20"-22.5" (width:300mm), 20"-22.5" (width:350mm). • Standard layout: 15"~16", 20"~22.5" expansion rim and a dusty collector.
Function	• Optional function: sidewall polishing and clean, tread circumference measurements, measure the thickness of remaining tread rubber, manually operation on polishing tire shoulder • Average polishing time: 3 mins.
RATED POWER	380V, 50Hz, 12kW