

Paket Vulkanisir Ban sistem Dingin - BAI

MESIN PEMARUT (BUFFING)



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Description	for 15"-22.5"
Dimensi (PxLxT)	1800X1700X1500 mm
Function	- Polishing the old pattern rubber to meet the needs of tire vulcanization - Radius of radian range is 400 ~ 800mm,also polish the appointed radian - Optional expansion rim: 15"-16",17.5"-19.5",20"-22.5", 20" - 22.5"(width:250mm), 20"-22.5"(width:300mm), 20"-22.5"(width:350mm). - Standard layout: 15"~16", 20"~22.5" expansion rim and a dusty collector. - Optional function: sidewall polishing and clean, tread circumferential measurements, measure the thickness of remaining tread rubber, manually operation on polishing tire shoulder - Average polishing time: 3 mins.
Rated Power	380V,50Hz, 12kW

MESIN UNTUK INSPEKSI PRODUK



Description	≤ 22.5"
Dimensi (PxLxT)	1500X1000x1100 mm
Function	- Put the tire on the machine, expanding the tire to suitable size for testing and repairing from the bead, air cylinder supply power of expanding and lifting - Tire can roll by electric, operator can control the speed and stop - Match with a safety lamp, improve the effective and quality of test and repair - It can be match with integral monorail.
Rated Power	220V,50Hz,950w