

Paket Vulkanisir Ban sistem Dingin - BAI

OVEN VULKANISASI		
 	Description	Φ1500 (Volume 4pcs), PID System Control, For 15"-22.5" tire
	Dimensi (PxLxT)	2800X2250 X2300 mm
	Function	- Automatic alarm, Automatic timing. - Automatic door and three triplock for safety 2pcs tires backup space for expanding output - PID system controls temperature, pressure, curing time. - Automatic compensation function on temperature, pressure - Electric/Oil/Steam heating. - Automatic PLC Touch Screen Controller
	Rated Power	380V,50Hz,30 kW
MESIN PENEMPELAN KEMBANG VULKANISIR		
Note : Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice! 	Description	for 15"-22.5"
	Dimensi (PxLxT)	1500X1200X2000 mm
	Function	- Pressure the tread on the surface of old tyre, and put the air out among the tread and cushion gum and tyre surface. - The thread pitch of pinch roller screw mandrel control the speed and pressure, make the pinch roller roll from the middle to both side. - Optional expansion rim : 15"-16", 17.5"-19.5", 20"-22.5", 20"-22.5"(width:250mm), 20"-22.5"(width:300mm), 20"-22.5"(width:350mm), 24"and welcome special size order. - Standard layout : 15"-16", 20"-22.5"expansion rim and tread cutting machine. - Optional function : control system of pre tightening force on the tread, automatic tread centration system, infrared ray tread centration system. - Average tire building time: 5 mins.
	Rated Power	380V,50Hz,2.5Kw