



BT-50(60) PVC HEAT SHRINK FILM EXTRUSION MACHINE

Usage:

The machine is suitable for blowing PVC heat shrinkable plastic film, which is widely used for packing foodstuff, garment, electric goods, daily-use articles etc

BT-50(60)
PVC heat shrink
Film extrusion machine

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



Main Technical Parameter

Model	BT-50	BT-60	Max. Film Output	20Kg/h	30Kg/h
Suitable Material	PVC	PVC	Cooling Blower	1.14Kw	1.5Kw
Width Range	400mm	550mm	Take Up Roller Width	600mm	800mm
Thickness	0.025-0.10mm	0.025-0.10mm	Effective Width	400mm	550mm
Screw Diameter	55mm	60mm	Take-up Motor	1.5kw	2.2Kw
Screw L/D Ratio	28:1 L/D	28:1 L/D	Take-up Speed	20m/min	20m/min
Screw/Barrel Material	38CrMoAlA	38CrMoAlA	Winding Roller Width	500mm	600mm
Heater Capacity	20Kw	20Kw	Max.Winding Width	400mm	400mm
Auto-Thermo Control	6Z	6Z	Winding Motor	16w/m	16w/m
Barrel Cooling Fan	0.3Kw	0.3Kw	Tank Electric Heat	8Kw	10Kw
Driving Motor	15Kw	18.5Kw	Machine Dimension	500X1500X3500mm	500X1500X3500mm
Die Diameter	45-100mm	60-120mm	Net Gross	1600Kg	1800Kg
Air Ring Diameter	280mm	350mm	Gross Weight	2000Kg	2200Kg