



Shrinkable Film Blowing Machine (For Printing Type) for PVC Material only

(Biji Plastik menjadi PVC shrink label dalam bentuk Roll)



Model : **WT-SJ-P-45/350**

The machine's set adopts to revolve a mold head and changes the Pin adjust soon and automatic constant temperature control etc. item technique, the production come out of product petrochemistry good, the degree of thickness even degree, clarity of thin film, neat degree, constringency rate...etc. various quality index signs attain printing class the technique standard of the thin film.

The machine's set organization tightly packed, the operation is easy, mainly from as follows part of constitute: Extruder machine, revolve a mold head, cool off breeze wreath, the first to lead, hot water box and already set set, the second lead(dynamolectric ascend and descend), double the work accept a machine and extrude a machine electricity to control a cabinet and assist a machine electricity to control a cabinet.

Note :
Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

Technical Specification

Type	WT-SJ-P 45/350
Suitable raw material	PVC
Film width[mm]	350
The thickness of film [mm]	0.025-0.08
Screw diameter[mm]	45
The machine head/mold head Diameter[mm]	Φ80
Power of thermo [KW]	13
refrigeration fan [KW]	0.25
Main motor power[KW]	15
diameter of air ring [mm]	Φ500
roller width(mm)	400
Take up power[KW]	1.5
Lead Production speed [meter/minutes]	8-35
Rewinding roll width[mm]	400
Re-winding roll diameter[mm]	600
Re-winding power (torque motor)	16N/M
Cooling blower power (kW)	1.1
Temperature control point	5