

PE HIGH & LOW-PRESSURE BLOWING FILM MACHINE

Characteristics:

Its extruder, cylinder and screw rods are made of quality alloy steel that have been nitridized and processed in a precision way. Hence it is sound in hardness, durable in corrosion resistance. The specially-designed screw is of sound quality in plasticizing, which helps increase the production capacity. It is applied to blowing the plastic films like low density polyethylene (LDPE), high density polyethylene (HDPE) and linear low density polyethylene (LLDPE). It is widely applied to producing the packing bags for foodstuff, clothing, rubbish bag and vest ones.

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!



OPTIONAL EQUIPMENT

1) AUTO LOADER 2) CAST ALUM HEATER 3) AIR SHAFT 4) ROTARY DIE DEVICE 5) BOUBLE SIDES WINDER 6) UP AND DOWN 7) PNEUMATIC DEVICE

MAIN TECHNICAL PARAMETER

Model	A50	A55	A65	A65-1
Diameter of Screw	φ50	φ55	φ60	φ65
Reduced diameter of Film (mm)	100-600	200-800	300-1000	400-1200
Single-face Thickness of Film (mm)	0.01-0.08	0.01-0.08	0.01-0.08	0.01-0.08
Max. Extrusion (Kg/h)	35	50	65	80
L/D	28:1	28:1	28:1	28:1
Power of Main Motor (kw)	11	15	18.5	22
Power of Traction Motor (Kw)	1.1	1.1	1.5	1.5
Heating Power (kw)	11	13	19	21
Outline Diameter (LxWxH) (mm)	5000x1600x3800	5600x2200x4700	6500x2300x5150	6500x2500x5150
Weight	1.8T	2.2T	2.6T	2.8T

Technical Parameters are Subject to Change Without Prior Notice!