

■ SJ-B50. 55. 65. 65-1 Rotary Machine Head Film Blowing Machine Set (PE Heat-shrinkable Film Blowing Machine)

■ CHARACTERISTICS

It is used for blowing high-low pressure polyethylene, which has been widely used for producing laminating film, packing film, agricultural covering film, bag or film for textile and clothing and other packing material. The main motor adopts frequency control of motor speed to improve the speed regulating stability of main motor and save electricity by 30%. The screw and material barrel adopt 38 chrome-molybdenum aluminum which has been nitrogen treated and the traction frame adopts lifting type. No matter what size the film is, big or small, it can achieve the best effect of cooling.



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

■ OPTIONAL EQUIPMENT

- | | |
|---------------------------|------------------------|
| 1) AUTO LOADER | 4) AUTO WINDER |
| 2) FILM SURFACE TREATER | 5) DOUBLE-LIP AIR RING |
| 3) HIGH SPEED NET CHANGER | |

MAIN TECHNICAL PARAMETER

Model	SJB50	SJB55	SJB65	SJB651
Screw Diameter	50mm	55mm	60mm	65mm
Screw Ratio (L/D)	28:1	28:1	28:1	28:1
Screw Speed	10-100r/min	10-100r/min	10-100r/min	10-100r/min
Power Of Main Motor	11Kw	15Kw	18.5Kw	22Kw
Max. Output	35Kg/h	50Kg/h	65Kg/h	80Kg/h
Max. Folding Width of Film	600mm	800mm	1000mm	1200mm
Single-Sided Thickness of Film	0.01-0.08mm	0.01-0.08mm	0.01-0.08mm	0.01-0.08mm
Total Power	22Kw	26Kw	30Kw	36Kw
Weight of Machine	2.5T	2.9T	3.4T	3.5T
Overall Dimensions	6200x2050x4700mm	6800x2500x5000mm	7200x2700x5800mm	7300x2900x5800mm

Technical Parameters are Subject to Change Without Prior Notice!