



PS FOAM SHEET EXTRUSION LINE

PS发泡片材机



特点及应用:

该生产线采用双机串联式高发泡片材生产工艺，生产的PS发泡片材是一种新型包装材料，不但有良好的隔热和缓冲性能，而且有珍珠般的外观色泽。具有防震、隔音、保温、防潮、安全卫生，可吸塑性等优点，经真空热成型，广泛应用于食品、水果、电子、日用品，五金制品等多种产品的包装及广告板等。

Characteristics & Application

Product Description: This PS foam sheet extrusion machine produce PS foam sheet, which is a kind of new-type packing with the features of shock proofing, sound insulating, heat preservation, damp proof, safety, and good plasticity. It is used widely in the packing of food, fruit, electronic product, daily necessities, hardware product, advertisement plate, etc.

主要技术参数 Main Technical Parameters

型号	Model	FS-FPP75/90	FS-FPP105/120	FS-FPP120/150
挤出机	Extruder	75/90	105/120	120/150
发泡倍率	Foaming Rate	12-20	12-20	12-20
制品宽度	Width of product (mm)	540-1200	540-1200	540-1200
剖切方式	Cutting mode	单剖或双剖 Single or double cutter		
制品厚度	Thickness of product (mm)	1.0-2.0	1.0-3.5	1.2-5.0
冷却方式	Cooling method	风冷和水冷 Air and water cooled		
产量	Output (kg/h)	60-90	150-220	250-320
装机容量	Installed Capacity (KW)	150	200	300
外形尺寸	Dimensions(L×W×H)(m)	18×5×2.8	20×6×2.8	25×6×3.2
总重量	Total Weight (T)	10	12	18

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!