

VGI

PE PP FILM GRANULATING PRODUCTION LINE COMPACTOR EUROPEAN SERIES



APPLICABLE PLASTIC MATERIAL:
PP, LDPE, LLDPE, HDPE, BOPP, etc (except PET)
PP Woven Bags, rolls film, sheets, raffia,
plastic foamed, plastic forming etc



		Technology Parameters					
Type		KOP89	KOP100	KOP150	KOP168	KOP200	KOP250
Capacity(t/h)		10-120	100-120	100-200	100-150	100-150	100-150
Energy consumption(kWh/kg)		0.2-0.35	0.2-0.35	0.2-0.35	0.2-0.35	0.2-0.35	0.2-0.35
Length(mm)		10,000	10,000	11,000	11,000	12,000	12,000
Width(mm)		6,200	6,200	6,200	6,200	6,200	6,200
Height(mm)		3,000	3,700	3,000	4,200	4,000	4,000
Compressor	Volume(L)	300	300	300	300	300	300
	Motor Power(kw)	22.40	30.75	70.40	60.100	100.100	140.100
	Screw Diameter(mm)	φ80	φ100	φ120	φ140	φ160	φ180
Extruder	L/D	30:40	30:40	30:40	30:40	30:40	30:40
	Motor power(kw)	55.75	55.75	100.100	100.200	200.200	200.200
Filter (optional)	Two position plate type	+	+	+	+	+	+
	Two position plate type	-	-	-	-	-	-
	Block flush screen type	-	-	-	-	-	-
	Automatic self-cleaning type	-	-	-	-	-	-
	Screw Diameter(mm)	φ100	φ100	φ100	φ100	φ100	φ100
Screw Extruder (optional)	L/D	40:40	40:40	40:40	40:40	40:40	40:40
	Motor power(kw)	22.40	40.00	55.75	70.40	100.100	140.100
	Water ring pelletizer	+	+	+	+	+	+
Cooling system (optional)	Water pelletizer	-	-	-	-	-	-
	Automatic water pelletizer	-	-	-	-	-	-
	Underwater pelletizer	-	-	-	-	-	-

400015002 alternative



SINGLE STAGE SYSTEM



Touch Screen
Controller

Note: Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice