

QJ-50C/QJ-65C

Automatic Extrusion Blow Molding Machine

GENERAL INTRODUCTION

QJ50C/QJ65C Extrusion Blow Molding Machine is applied to produce hollow containers for medicine, foodstuff, beverage, automobile parts, household appliance and daily necessities.

FEATURE:

- 1、Adopt high-speed design, reasonable structure, specially fit to produce containers from 1–1500ml.
- 2、Electric control part adopt famous brands
- 3、Pneumatic system adopt famous brand components, respond quickly, works steadily, long lifetime.
- 5、Durable and less noise, lifetime is about 10 years
- 6、Produce different weights and volumes containers at the same time.

Parameter	Unit	QJ50C	QJ65C
Suitable Raw Material	/	PE, PP, PS, PA, EVA etc	PE, PP, PS, PA EVA etc
Max. Volume of Product	L	0.5	1.5
Screw Diameter	mm	50	65
Screw L/D Ratio	L/D	23:1	23:1
Screw Speed	r.p.m	15~90	15~90
Plasticizing Capacity	Kg/hr	35	55
Extruder Power	Kw	7	11
Heater Power	Kw	7	15
Mould frame Quantity	Set	2	2
Mould Number	Set	4	4
Clamping Stroke	mm	100	150
Compressed Air Required	Mpa	0.7	0.7
Machine Weight	Kg	1500	2200
Machine Dimension	m	2.5*1.0*1.7	3.3*1.5*2.0

Note : Due to continual improvement, specifications are subject to change without notification. Please refer to the latest actual machine.



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!