



1. Plastik Sheet Extruder



• EXTRUDER MAIN TECHNICAL PARAMETER:

1. Effective sheet width : ≤ 670 mm
2. Sheet thickness : $0.3 \sim 2.0$ mm
3. max extruding volume : ± 200 Kg/hour
4. Raw material : PP/PS/PE (HIPS) Granule/Powder
5. Power Supply : 380V /50HZ, 3phase
6. Complete machine power: 65 kW
7. Overall dimension : 11000×2000×1800mm
8. Weight : ± 5800 Kg

• MAIN PART:

1. HOPPER :
 - 1.1. Quantity : 1pc
 - 1.2. Material : iron
2. GEAR BOX :
 - 2.1 Quantity : 1pc
 - 2.2 Function : Hard-toothed surface
 - 2.3 Brand : zhejiang duling
3. MOTOR :
 - 3.1 Quantity : 1pc
 - 3.3 Function : 960turn/min, Inverter control
 - 3.4 Brand : Shanghai dedong
4. SCREW/BARREL :
 - 4.1 Quantity : 1pc
 - 4.2 Material : 38CrMoAl; hardness ≥ 940 HV
 - 4.3 Screw parameter : main screw $\phi 110\text{mm} \times 3300\text{mm}$
 - 4.4 Barrel thickness : 25mm
 - 4.5 Brand : Zhejiang zhoushan
 - 4.6 Heating system : 5 areas , Aluminum casted heater

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

