



Hydraulic automatic screen changer

Method	Two station hydraulic automatic changing screen
Material	Alloy steel
Mobile metal plate material	Carburizing steel
Filter Screen	Two sets with diameter 120mm
Screen Material	5CrNiMo steel after heating treatment
Power	3kW
Screen Changer Time	≤2s

Nose and Mold

Mold Material	Mold steel 40Cr in good quality
Mold Width	600mm
Dimension of Final Sheet	Width 600mm Thickness 6mm (Thickness can be adjusted)



Electrical Cabinet

Frequency Inverter	ABB
Temperature Controller	Omron
Contactora	Schneider
Relay	Schneider

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



Three-roller Calender

Calender quantity	3pcs
Calender diameter	Φ450mm
Material	40CrMo
Effective length	670mm
Drive motor power	1.5KW*3sets
Water pump power	7kw
Roller Spacing Adjust Range	1-50mm



Cooling Bracket and Cutting Edge

Material	Rollers made of stainless Steel with good quality
Length of Bracket	10000mm
Diameter of Roller	φ 70mm
Cutting Edge Device	One set with cutting blade (scraps can be used in recycle production)

Two-roller Haul-off Machine

Haul off method	Two groups four rubber roller
Roller material	Made of rubber roller in good quality
Roller Diameter	Φ240
Motor Power	1.5kw control speed by frequency inverter
Planetary Cycloid Reducer	One set

Stacker

