



# STG-U SERIES HOPPER DRIER

## Application

- It can save energy by 27-65%;
- It can avoid plastic granule second moisture absorption after drying when directly linked the material inlet of the main machine;
- Great in drying ability, and it can increase injection speed rate;
- The quality of finished products can be improved.

**Note :**  
Due to keeping innovation,  
the specification and  
Machine pictures or color  
are subject to alteration  
without notice!



## Main technical parameter

| model     | (L)    | (kg)     | Power (kw) |       |
|-----------|--------|----------|------------|-------|
|           | volume | Capacity | Heater     | Motor |
| STG-U8    | 8      | 5        | 1.2        | 0.04  |
| STG-U16   | 16     | 10       | 1.4        | 0.06  |
| STG-U20   | 20     | 12       | 1.6        | 0.06  |
| STG-U25   | 25     | 15       | 1.8        | 0.06  |
| STG-U40   | 40     | 25       | 2.6        | 0.06  |
| STG-U80   | 80     | 50       | 3.9        | 0.12  |
| STG-U125  | 125    | 75       | 4.8        | 0.12  |
| STG-U160  | 160    | 100      | 5.4        | 0.25  |
| STG-U250  | 250    | 150      | 9          | 0.37  |
| STG-U315  | 315    | 200      | 12         | 0.37  |
| STG-U400  | 400    | 250      | 15         | 0.55  |
| STG-U500  | 500    | 300      | 18         | 0.55  |
| STG-U800  | 800    | 500      | 24         | 0.75  |
| STG-U1250 | 1250   | 800      | 36         | 1.1   |