

BALL MILL

The ball mill is the key equipment for the material being broken, then grinding. Ball mill is widely used in black and non-ferrous mineral processing, building materials, chemicals and glass-ceramic and other production industries, as for a variety of grinding of ores and other materials can be carried out for dry or wet grinding.



Model	Speed (r/min)	Ball Weight (t)	Input Size (mm)	Capacity(t/h)	Power (KW)	Weight (t)
φ 900*1800	38	1.8	≤20	0.65-2	18.5	4.6
φ 900*3000	38	2.7	≤20	1.1-3	22	5.6
φ 1200*2400	32	3.6	≤25	1.5-3.5	30	12
φ 1200*3000	32	5	≤25	1.6-5	37	12.8
φ 1200*4500	32	6	≤25	1.6-6.8	55	13.8
φ 1500*3000	27	6.8	≤25	2-5	75	15.6
φ 1500*4500	27	14	≤25	3-6	110	21
φ 1500*5700	27	15	≤25	3.5-8	132	24.7
φ 1830*3000	24	11	≤25	4-10	180	28
φ 1830*4500	24	15	≤25	4-13	180	32
φ 1830*6400	24	23	≤25	6.5-15	210	34.6
φ 1830*7000	24	25	≤25	7.5-17	245	36
φ 2100 × 3000	23.7	15	≤25	6.5-36	155	34
φ 2100 × 4500	23.7	24	≤25	8-43	245	42
φ 2100 × 7000	23.7	26	≤25	8-48	280	50
φ 2200*5500	21.7	30	≤25	10-22	370	48.5
φ 2200*6500	21.7	31	≤25	14-26	380	52.8
φ 2200*7000	21.7	34	≤25	15-28	380	54
φ 2200*7500	21.7	35	≤25	16-30	380	56
φ 2400 × 3000	21	23	≤25	7-50	250	55
φ 2400 × 4500	21	30	≤25	8.5-60	320	60
φ 2400*7000	21	54	≤25	20-32	475	67
φ 2700 × 3600	20.5	39	≤25	12-80	400	74
φ 2700 × 4500	20.5	43.5	≤25	12-90	500	82
φ 3200 × 4500	18	68.5	≤25		800	126

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!