



USE: The roller crusher work reliable, easy to maintain, low costs for operation, the feed granularity is adatable. According to roller quantity, there are double-roller crushers which are widely used to process brittle and flexible materials in cement, metallurgy, chemical industry, soil, clay industry, coal industry etc.

MAIN TECHNICAL PARAMETER :

Model	TYPE	Dia. X Length (mm)	Max. Feed Size (mm)	Material Nesting (mm)	Capacity (Tons/hour)	Roller Speed (rpm)	Motor Power (kW)	Weight (Kgs)
MILLER	2PG 300x300	300x300	14-17	1-5	3-8	180	7.5	1200
	2PG 400x250	400x250	20-40	1-8	5-10	200	11	1500
	2PG 500x450	500x450	23-40	10-15	10-35	180	15	3800
	2PG 610x400	610x400	≤40	13-35	15-40	80	30	6000
	2PG 750x500	750x500	≤40	15-35	20-50	60	37	9000
	2PG 900x500	900x500	≤40	15-35	30-60	50	45	14000
	2PG 900x700	900x700	≤40	15-35	40-70	50	55	16000
	2PG 1200x1000	900x700	≤40	15-35	50-80	70	75	19000
COARSE	2PGC 450x500	450x500	80-200	1-100	20-55	64	11	2200
	2PGC 600x750	600x750	100-400	1-125	30-120	50	22/37	7100
	2PGC 1200x1500	1200x1500	150-600	≤100	400-600	70.5	90/110	32200



Note :
Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!