

▼ GZD、 GZD / ZSW Vibrating Feeder

Our Vibrating Feeder has GZD Series and ZSW Series.

GZD Series Vibrating Feeder adopts vibration motor as the source of vibration, which has features of simple structure, high capacity, low maintenance. It can be widely used in the fields of metallurgy, construction, stone crushing, etc.

While, ZSW Series Vibrating Feeder adopts eccentric block as the source of vibration, gear drive by turns which has low vibrating noise, smooth operation, long usage. It can also pre-screening fine raw materials which makes higher efficiency, the designing of adjustable fence can prevent the materials from blocking in the gap.



Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

| Main Specification

Model	Max.Feeding Size (mm)	Capacity (t/h)	Motor Power Pole	Power (kw)	Installation Angle (°)	Size of Funnel (mm)
GZD-180×80	300	30-80	4	2×1.5	0-10	1800×800
GZD-300×90	400	40-100	4	2×2.2	0-10	3000×900
ZSW-300×90	450	50-150	6	7.5	0-10	3000×900
ZSW-380×96	500	120-210	6	11	0-10	3800×960
ZSW-420×110	650	180-400	6	15	0-10	4200×1100
ZSW-490×110	650	250-480	6	15	0-10	4900×1100
ZSW-490×130	800	300-550	6	22	0-10	4900×1300
ZSW-600×130	800	340-600	6	30	0-10	6000×1300
ZSW-600×160	1050	400-800	4	37	0-10	6000×1600