

FULLY AUTOMATIC ELECTRICAL- HEATED STEAM BOILER



电磁阀
controller valve



液位控制器
liquid-level controller



水泵
pump



水箱浮球阀
Water tank floating
ball valve



压力表
pressure meter

The outline patent
No. is 02304952.9



液位浮球阀
Liquid level floating
ball valve



安全阀
safety valve



电热管
heating tube

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

The main performance & parameters

	LDR 0.09- 0.4(0.7)-1	LDR 0.1- 0.4(0.7)-1	LDR 0.125- 0.4(0.7)-1	LDR 0.15- 0.4(0.7)-1	LDR 0.135- 0.4(0.7)-1	LDR 0.15- 0.4(0.7)-1
Heating power	kW	72	80	100	108	120
Rated evaporation rate	kg/h	90	100	125	135	150
Rated steam pressure	Mpa	0.4 (0.7)				
Rated steam temperature	°C	151 (171)				
Nominal size of water inlet/steam outlet pipe	mm	15/40				
Outline dimension	mm	980 x 800 x 1680				
Power supply	Volt	380				

Features:

It manufactures the most safe and ideal steam boilers with the advanced, fully automatic high & low water level cut-off device, relief valve, pressure passed X-ray check. It proves to have reliable quality after the examination

top security techno-loggy with performance. it is attached with water tank, high pressure pump, controller, the durable calorific wire for water level gauge, each boiler welding seam has and confirmation from Special Equipment & Inspection Department.



LDR 0.09~0.15 - 0.4 (0.7)-1