



Ring Hammer Crusher

Ring hammer crusher (hammer broken) is suitable for crushing all kinds of brittle materials such as coal, coal gangue, coke, slag, red sandstone, shale, loose limestone and so on. The compressive strength of the material does not exceed 100Mpa, surface water is not more than 15%.

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



Model	Feeding Size (mm)	Output Size (mm)	Capacity (t/h)	Speed (r/min)	Motor		Weight(t)	Overall Dimension (mm)
					Type	Power		
PCH0402	≤ 200	≤ 30	8-12	960	Y132M2-6	5.5	0.8	810x890x560
PCH0404	≤ 200	≤ 30	16-25	970	Y160L-6	11	1.05	980x890x570
PCH0604	≤ 200	≤ 30	22-33	970	Y180L-6	15	1.43	1050x1270x800
PCH0606	≤ 200	≤ 30	30-60	980	Y225M-6	30	1.77	1350x1270x1080
PCH0808	≤ 200	≤ 30	70-105	740	Y280M-8	45	3.6	1750x1620x1080
PCH1010	≤ 300	≤ 30	160-200	740	Y315M2-8	90	6.1	2100x2000x1340
PCH1016	≤ 300	≤ 30	300-350	740	JS-128-8	155	9.2	2700x2000x1350
PCH1016	≤ 300	≤ 30	620-800	740	Y450-8	355	15.0	4965x2500x1600
PCH1322	≤ 300	≤ 30	800	595	Y450L-8	400	24.9	6333x3295x2505