

▼ | WKS Series High-efficiency Cone Crusher

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

To obtain ideal product of low cost, easy operation and maintenance, WKS Series High-efficiency Cone Crusher is the best choice. After being optimized, structure of WKS series Simons cone crusher is more reasonable and perfect, its technology is more advanced in manufacturing, installation, operation, maintenance, etc. Its application in fields of mining, metallurgy, refractory, construction debris has been proved very well.

WKS series high-efficiency cone crusher has many chambers, from fixed crusher to mobile crushing station, to meet different customer's needs. It have shown a good performance in crushing, fine crushing and ultrafine crushing operations. New laminate design of crushing plate and mantle plate have a higher efficiency; unique cavity cleaning system reduces maintenance costs significantly; high performance brings high profits to our partner.

| Main Specification

Standard:

Model		WKS75 -B			WKS160-B			WKS250-B			WKS350-B		
Specs		3Ft900			4 1/4Ft 1275			5 1/2Ft 1650			7Ft 2134		
Cavity Type		narrow	medium	wide	narrow	medium	wide	narrow	medium	wide	narrow	medium	wide
TheSmallestDischarge SizeRecommended(mm)		9	13	25	13	16	25	16	22	38	19	25	38
Corresponding FeedingSize	B (close)side (mm)	83	159	163	109	188	238	188	213	331	253	303	425
	B (open) (mm)	102	175	178	137	210	259	209	241	368	278	334	460
Capacity(t/h)		45-91	50-120	59-163	109-181	132-253	172-349	181-327	258-417	299-635	381-726	608-998	789-1270
MotorPower(kw)		6P-75			6P-160			6P-250			6P-350		

Short Head:

Model		WKS75 -D			WKS160-D			WKS250-D			WKS350-D		
Specs		3Ft 914mm			4 1/4Ft 1295mm			5 1/2Ft 1676mm			7Ft 2134mm		
Cavity Type		narrow	medium	wide	narrow	medium	wide	narrow	medium	wide	narrow	medium	wide
TheSmallestDischarge SizeRecommended(mm)		3	3	6	3	6	16	5	6	13	5	10	16
Corresponding FeedingSize	D(close)side (mm)	13	33	51	19	54	98	35	54	117	51	95	152
	D(open) (mm)	40	60	76	64	89	133	70	89	133	105	133	203
Capacity(t/h)		27-90	30-100	31-110	36-163	82-163	109-227	90-209	136-281	190-336	190-408	354-508	454-599
MotorPower(kw)		6P-75			6P-160			6P-250			6P-350		