

▼ | Single Cylinder Hydraulic Cone Crusher

The single cylinder hydraulic cone crusher is applicable to mineral fine grinding and ultra fine grinding. This series of crushers are divided into HCX, HCM used in coarse crushing, secondary crushing, and fine crushing. It is easy for crushing the material to the required size range, and meets the production needs of customers.



| Main Specification

HCX-high Cone

Model	Cavity mould	Max.Feeding Size(mm)	Outprt size(mm)	Eccentricity	Capacity (t/h)	Power(kw)
HCX90	C	100	12-25	大	45-110	90
	M	65	10-18	中	35-75	
	F	35	8-12	小	25-55	
HCX160	C	150	20-35	大	75-105	160
	M	90	15-30	中	60-90	
	F	50	10-25	小	40-65	
HCX250	C	180	20-40	大	110-200	250
	M	110	15-35	中	100-190	
	F	75	10-25	小	90-160	
HCX315	C	240	20-50	大	180-320	315
	M	135	20-40	中	160-300	
	F	90	15-35	小	150-280	
HCX560	C	260	20-50	大	350-960	560
	M	160	20-40	中	300-800	
	F	95	15-35	小	260-650	

HCM-high cone

Model	Cavity mould	Max.Feeding Size(mm)	Outprt size(mm)	Capacity (t/h)	Power(kw)
HCM90	C	220	20-35	60-110	90
HCM160	C	300	30-50	12-240	160
HCM250	C	400	35-55	240-360	250
HCM315	C	500	45-70	350-500	315

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!