

PY Series Spring Cone Crusher



Applications:

SECONDARY/TERTIARY CRUSHING:

- Mining
- Aggregate
- Demolition
- Industrial
- Construction
- Environmental

Advantages:

- Reliable construction
- High productivity
- Easy adjustment
- Low operation cost

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

PY series spring cone crusher

Mode	Diameter of Bottom End of Conical Crushing Head (mm)	Max Feeding Size(mm)	Adjustable Range Of Discharge Opening (mm)	Crushing Capacity (t/h)	Motor Power (kW)	Rev.of Eccentric Shaft(r/min)	Weight (t)	Overall Dimension (LxWxH)(mm)
PYB900	900	115	15-50	50-90	55	333	11.2	2692x1640x2350
PY2900	900	60	5-20	20-65	55	333	11.2	2692x1640x2350
PYD900	900	50	3-13	15-50	55	333	11.3	2692x1640x2350
PYB1200	1200	145	20-50	110-168	110	300	24.7	2790x1878x2844
PYZ1200	1200	100	8-25	42-135	110	300	25	2790x1878x2844
PYD1200	1200	50	3-15	18-105	110	300	25.3	2790x1878x2844
PYB1750	1750	215	25-50	280-480	160	245	50.3	3910x2894x3809
PYZ1750	1750	185	10-30	115-320	160	245	50.3	3910x2894x3809
PYD1750	1750	85	5-13	75-230	160	245	50.2	3910x2894x3809
PYB2200	2200	300	30-60	590-1000	260-280	220	80	4622x3302x4470
PYZ2200	2200	230	10-30	200-580	260-280	220	80	4622x3302x4470
PYD2200	2200	100	5-15	120-340	260-280	220	81.4	4622x3302x4470