



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

■ 机组简介：华鑫/康明斯系列柴油发电机组是我公司多年来在品牌中销售最好的一款产品，也是获得口碑最好的一款产品。该产品选用著名品牌康明斯B、C、L、N、K系列发动机做为动力配成的柴油发电机组，该类机组具有排放低、消耗低、五倍于国产机的大修期，优良的三包和合理的价格。

■ INTRODUCTION:Huaxin/Cummins diesel generator set is the Department of our company over the years the best selling brands in a product,the best word-of-mouth has also been a product,The selection of famous brand products Cummins B、C、L、N、K series engine as a pair of diesel power generating units,such units with low emissions,low consumption,five times in the overhaul period of China-made machine,excellent warranty and reasonable price.

机组型号 Genset Model	50HZ COSφ=0.8,400/230V 3P 4W		康明斯柴油发动机 Cummins Diesel Engine										康明斯柴油发动机 Cummins Diesel Engine										华鑫发电机 HX Alternator					外形尺寸(mm) Overall Size	毛重(kg) Gross Weight
	额定功率KW Prime Power	备用功率KW Standby Power	型号 Model	型式 Type	额定功率KW Rated Power	进气方式 Intake Type	气缸数 No. of Cylinder	缸径×冲程(mm) Bore ×Stroke	活塞速度(m/s) Piston Speed	压缩比 Compression Ratio	机械调速率 Mechanical Governor Rate	电子调速率 Electronic Governor Rate	噪音(dBA) Noise Level	排气温度(℃) Exhaust Temperature	机油容量(L) Exhaust Oil Capacity	燃油消耗量(L/h) Rated Fuel Consumption	排量(L) Displacement	额定功率KW Rated Power	效率 Power Efficiency	电压调节 Voltage Regulation	励磁方式 Excitation Type	绝缘等级 Insulation Class							
HC16GF	16/20	17.6/22	4B3.9-G1	water-cooled,4-cycle,direct injection, wet cylinder liner,150 Orpm	24	Natural	4.L	102×120	6	16.8:1	≤5%	≤1%	≤96	475	11	6.7	3.9	16/20	84.20%	≤±1.5	Brushless	H	1840×760×1430	780					
HC20GF	20/25	22/27.5	4B3.9-G1		24	Natural	4.L	102×120	6	16.8:1	≤5%	≤1%	≤96	475	11	6.7	3.9	20/25	85.80%	≤±1.5	Brushless	H	1840×760×1430	800					
HC22GF	22/27.5	24.2/30.25	4B3.9-G1		24	Natural	4.L	102×120	6	16.8:1	≤5%	≤1%	≤96	475	11	6.7	3.9	22/27.5	85.80%	≤±1.5	Brushless	H	1840×760×1430	8360					
HC24GF	24/30	26.4/33	4BT3.9-G1		36	Turbocharged	4.L	102×120	6	16.5:1	≤5%	≤1%	≤96	475	11	9.3	3.9	24/30	86.20%	≤±1.5	Brushless	H	1840×760×1430	8460					
HC28GF	28/35	30.8/38.5	4BT3.9-G1		36	Turbocharged	4.L	102×120	6	16.5:1	≤5%	≤1%	≤96	475	11	9.3	3.9	28/35	86.60%	≤±1.5	Brushless	H	1840×760×1430	896					
HC32GF	32/40	35.2/44	4BT3.9-G1		36	Turbocharged	4.L	102×120	6	16.5:1	≤5%	≤1%	≤96	475	11	9.3	3.9	32/40	86.60%	≤±1.5	Brushless	H	1840×760×1430	906					
HC34GF	34/42.5	37.4/46.75	4BT3.9-G1		36	Turbocharged	4.L	102×120	6	16.5:1	≤5%	≤1%	≤96	475	11	9.3	3.9	34/42.5	86.60%	≤±1.5	Brushless	H	1840×760×1430	880					
HC40GF	40/50	44/55	4BTA3.9-G2		50	Turbocharged	4.L	102×120	6	16.5:1	≤5%	≤1%	≤96	475	11	11.5	3.9	40/50	88.20%	≤±1.5	Brushless	H	1900×760×1489	1030					
HC48GF	48/60	52.8/66	4BTA3.9-G2		50	Turbocharged	4.L	102×120	6	16.5:1	≤5%	≤1%	≤96	475	11	11.5	3.9	48/60	88.50%	≤±1.5	Brushless	H	1900×760×1489	1050					
HC58GF	58/72.5	63.8/79.75	6BTS.9-G1		92	Turbocharged	6.L	102×120	6	16.5:1	≤5%	≤1%	≤96	510	16.4	16.7	5.88	58/72.5	89.90%	≤±1.5	Brushless	H	2150×830×1496	1215					
HC68GF	68/85	74.08/93.5	6BTS.9-G1		92	Turbocharged	6.L	102×120	6	16.5:1	≤5%	≤1%	≤96	510	16.4	19.6	5.88	68/85	90.20%	≤±1.5	Brushless	H	2150×830×1496	1255					
HC80GF	80/100	88/110	6BTS.9-G1		92	Turbocharged	6.L	102×120	6	16.5:1	≤5%	≤1%	≤96	510	16.4	23.1	5.88	80/100	90.30%	≤±1.5	Brushless	H	2150×830×1496	1300					
HC96GF	96/120	105.6/132	6BTA5.9-G2		110	Turbocharged	6.L	102×120	6	16.5:1	≤5%	≤1%	≤96	601	16.4	27.5	5.88	96/120	90.60%	≤±1.5	Brushless	H	2150×830×1496	1335					
HC112GF	112/140	123.2/154	6BTA5.9-G2		120	Turbocharged	6.L	102×120	6	16.5:1	≤5%	≤1%	≤96	601	16.4	32.2	5.88	112/140	91.70%	≤±1.5	Brushless	H	2350×830×1496	1425					
HC128GF	128/160	140.8/176	6CTA8.3-G2		163	Turbocharged	6.L	114×135	6.8	16.8:1	≤5%	≤1%	≤96	638	20	36.4	8.27	128/160	92.30%	≤±1.5	Brushless	H	2450×850×1516	1695					
HC144GF	144/180	158.4/198	6CTA8.3-G2		163	Turbocharged	6.L	114×135	6.8	16.8:1	≤5%	≤1%	≤96	638	20	40.9	8.27	144/180	92.50%	≤±1.5	Brushless	H	2450×850×1516	1815					
HC160GF	160/200	176/220	6CTAA8.3-G2		183	Turbocharged	6.L	114×135	6.8	16.8:1	≤5%	≤1%	≤96	640	20	44.6	8.27	160/200	92.40%	≤±1.5	Brushless	H	2540×945×1550	1874					
HC184GF	184/230	202.4/253	6CTAA8.3-G2		220	Turbocharged	6.L	114×135	7.6	15:1	≤5%	≤1%	≤100	541	20	51.4	8.9	184/230	92.60%	≤±1.5	Brushless	H	2540×945×1550	2020					
HC200GF	200/250	220/275	6CTAA8.3-G2		220	Turbocharged	6.L	114×135	7.6	15:1	≤5%	≤1%	≤100	541	20	55.8	8.9	200/250	92.70%	≤±1.5	Brushless	H	2540×945×1550	2080					
HC240GF	240/300	264/330	MTAA11-G3		282	Turbocharged	6.L	125×147	7.6	14.5:1	≤5%	≤1%	≤100	648	34	66.9	10.8	240/300	93.00%	≤±1.5	Brushless	H	3150×1120×1630	2970					
HC260GF	260/325	286/357.5	NTA855-G2		283	Turbocharged	6.L	140×152	7.6	14:1	≤5%	≤1%	≤100	563	36.7	72	14	260/325	93.50%	≤±1.5	Brushless	H	3100×1100×1635	3198					
HC280GF	280/350	308/385	NTA855-G2A		313	Turbocharged	6.L	140×152	7.6	14:1	≤5%	≤1%	≤100	563	36.7	77	14	280/350	93.50%	≤±1.5	Brushless	H	3100×1100×1635	3198					
HC304GF	304/380	334.4/418	NTAA855-G7		343	Turbocharged	6.L	140×152	7.6	14:1	≤5%	≤1%	≤100	515	36.7	84	14	304/380	93.70%	≤±1.5	Brushless	H	3250×1190×1700	3200					
HC320GF	320/400	352/440	NTAA855-G7A		370	Turbocharged	6.L	140×152	7.6	14:1	≤5%	≤1%	≤100	515	36.7	94	14	320/400	93.40%	≤±1.5	Brushless	H	3300×1150×1170	3260					
HC360GF	360/450	396/495	KTA19-G3		407	Turbocharged	6.L	159×159	7.9	14.5:1	≤5%	≤1%	≤100	532	50	98	18.9	360/450	93.80%	≤±1.5	Brushless	H	3500×1375×1980	3950					
HC400GF	400/500	440/550	KTA19-G4		446	Turbocharged	6.L	159×159	7.9	14.5:1	≤5%	≤1%	≤100	84.3	50	107	18.9	400/500	94.30%	≤±1.5	Brushless	H	3500×1375×1980	3950					
HC450GF	450/562.5	495/618.75	KTA19-G5		470	Turbocharged	6.L	159×159	7.9	13.5:1	≤5%	≤1%	≤101	490	50	128	18.9	488/610	94.90%	≤±1.5	Brushless	H	3700×1750×2030	4200					
HC500GF	500/625	550/687.5	KTA19-G6A		554	Turbocharged	6.L	159×159	7.9	13.5:1	≤5%	≤1%	≤101	490	50	134	18.9	500/625	95.10%	≤±1.5	Brushless	H	3700×1750×2030	4200					
HC600GF	600/750	660/825	KTA38-G2		664	Turbocharged	6.L	159×159	7.9	16.5:1	≤5%	≤1%	≤102	552	135	170	37.8	600/750	93.30%	≤±1.5	Brushless	H	4490×1630×2430	7800					
HC640GF	640/800	704/880	KTA38-G2A		813	Turbocharged	12.V	159×159	7.9	16.5:1	≤5%	≤1%	≤102	552	135	182	37.8	648/810	94.40%	≤±1.5	Brushless	H	4490×1630×2430	8500					
HC728GF	827/910	800.8/1001	KTA38-G2A		813	Turbocharged	12.V	159×159	7.9	16.5:1	≤5%	≤1%	≤102	552	135	204	37.8	752/940	95.00%	≤±1.5	Brushless	H	4490×1630×2430	8560					
HC800GF	800/1000	880/1100	KTA38-G5		880	Turbocharged	12.V	159×159	7.9	14.5:1	≤5%	≤1%	≤103	513	135	201	37.8	824/1030	95.10%	≤±1.5	Brushless	H	4510×1850×2450	9020					
HC900GF	900/1125	990/1238	KTA38-G9		990	Turbocharged	12.V	159×159	7.9	13.9:1	≤5%	≤1%	≤103	527	135	207	37.8	908/1135	95.50%	≤±1.5	Brushless	H	4850×1850×2500	9400					
HC1000GF	1000/1250	1100/1375	KTA50-G3		1115	Turbocharged	12.V	159×159	8.3	13.9:1	≤5%	≤1%	≤103	475	177	261	50.3	1008/1260	94.90%	≤±1.5	Brushless	H	4950×2080×2560	10120					
HC1200GF	1200/1500	1320/1650	KTA50-G8		1298	Turbocharged	16.V	159×159	7.9	13.9:1	≤5%	≤1%	≤103	482	204	205	50.3	1240/1550	95.70%	≤±1.5	Brushless	H	5400×2195×2560	10600					