

Powered by Perkins

Gen-set Model	Prime power		Standby power		Engine Model	Alternator Model
	kw	kva	kw	kva	Perkins	Stamford
SP-7.2	7	9	8	10	403D-11G	PI044E
SP-10.4	10	13	11	14	403D-15G	PI044F
SP-16	16	20	18	22	404D-22G	PI144D
SP-20	20	25	22	28	404D-22TG	PI144E
SP-24	24	30	26	33	1103A-33G	PI144G
SP-36	36	45	40	50	1103A-33TG1	PI144K
SP-48	48	60	53	66	1103A-33TG2	UCI224E
SP-52	52	65	57	72	1104A-44TG1	UCI224F
SP-64	64	80	70	88	1104A-44TG2	UCI224G
SP-80	80	100	88	110	1104C-44TAG2	UCI274C
SP-109	108	135	119	149	1106A-70TAG1	UCI274E
SP-120	120	150	132	165	1106A-70TAG2	UCI274F
SP-147	145	181	160	199	1106A-70TAG3	UCI274G
SP-166	160	200	176	220	1106A-70TAG4	UCI274H
SP-182	180	225	198	248	1306C-E87TAG4	UCD274J
SP-200	200	250	220	275	1306C-E87TAG6	UCD274K
SP-280	280	350	308	385	2206C-E13TAG2	HC444E
SP-320	320	400	352	440	2206C-E13TAG3	HC444F
SP-364	360	450	396	495	2506C-E15TAG1	HC544C
SP-400	400	500	440	550	2506C-E15TAG2	HC544C
SP-473	470	588	517	646	2806C-E18TAG1A	HC544E
SP-520	520	650	572	715	2806A-E18TAG2	HC544F
SP-640	640	800	704	880	4006-23TAG3A	HCI6G1
SP-724	724	905	796	996	4008TAG1A	HCI6H1
SP-818	800	1000	880	1100	4008TAG2A	HCI6J1
SP-1002	1000	1250	1100	1375	4012-46TWG2A	LV6G
SP-1091	1100	1375	1210	1513	4012-46TWG3A	PI7B
SP-1204	1200	1500	1320	1650	4012-46TAG2A	PI7C
SP-1364	1360	1700	1496	1870	4012-46TAG3A	PI7D
SP-1480	1480	1850	1628	2035	4016TAG1A	PI7E
SP-1646	1600	2000	1760	2200	4016TAG2A	PI7F

Unit Electric Performance

Rated power factor : 0.8 lagging
Rated Voltage : 400/230V
Rated frequency : 50Hz if need 60Hz please contact us for more information.
Gen-set provides continuous power with 10% overload for 1 hour in 12 hours duration

Note :
 Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!