

MAS MAGNETICS

MAS Baiyun—YC Dry Drum Magnetic Separator

◆ Models : YC Dry Drum Magnetic Separator

It can attract dry magnetic powder from the non-magnetic materials continuously and automatically.



◆ Applications

It can be widely arranged in the lines such as it can be grinding, fire-proof material, foodstuff, feed, building material, ceramics, raw material for glass, renewable rubber powder, PVC powder, quartz sand, and chemical industry and so on. Feeding capacity can be adjusted to meet the different granularity requirement. It is characteristic with exempt-maintenance, energy saving, cost-lower, safety and reliability.

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

◆ Main Dimension and Technical Data

Model	External Size(mm)	Drum Spec (mm)	Magnetic Intensity(GS)	Quantity of Roller	Productivity (T/h)	Granularity Limited(mm)	Motor Power(kw)
YC-40- I	840x460x660	300x400	≥3800	1	≤0.6	≤5	0.55
YC-60- I	1120X710X930	400x600	≥4000	1	≤1.5	≤5	0.55
YC-60- II	1360x925x1240	320x600	first roller≥1000 second roller≥4000	2	≤2	≤5	1.5
YC-80- I	1470x820x1040	400x800	≥4000	1	≤2	≤8	0.75
YC-80- II	1710x1220x1570	400x800	first roller≥1000 second roller≥4500	2	≤2.5	≤8	1.5
YC-100- I	1590x1020x1240	500x1000	≥4500	1	≤2.5	≤10	1.1
YC-100- II	1910x1420x1770	500x1000	first roller≥1000 second roller≥4500	2	≤4	≤10	2