



MAGNETIC SEPARATOR



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Magnetic ore separator is applicable for wet magnetic separation of materials such as magnetite, pyrrhotite, roasted ore and ilmenite whose size is less than 3mm and also used for iron removal operation of materials such as coal, nonmetalliferous ore and construction material and so on.

Model	size of barrel		Capacity (t/h)	Rotation (r/min)	Power (kw)	(kg) Weight
	Diameter (mm)	Length (mm)				
CTB618	600	1800	18~35	40	2.2	1655
CTB712	750	1200	12~30	35	3	1682
CTB718	750	1800	20~45	35	3	1992
CTB918	900	1800	28~60	27	4	3162
CTB924	900	2400	38~80	27	4	3887
CTB1018	1050	1800	36~72	22	4	3801
CTB1024	1050	2400	52~100	22	5.5	4319
CTB1030	1050	3000	64~125	22	7.5	4976
CTB1218	1200	1800	55~95	19	7.5	5263
CTB1224	1200	2400	65~110	19	7.5	5927
CTB1230	1200	3000	85~120	19	7.5	6325
CTB1530	1500	3000	95~160	16	11	8665
CTB1540	1500	4000	120~190	16	11	9871