

YGFS Various Crusher Combined Crushing Plant Series

Economical and practical mobile crusher, fitting for the medium and small plant's clients, Full-automatic and self-loading multifunctional integration system including convey and screening, Independent crushing system.



Specification and Technical Parameter

Parameter Model	Length L1(mm)	Width B1 (mm)	Height H1 (mm)	Max. Height H2 (mm)	Max. width B2 (mm)	Belt of conveyor H3 (mm)	Wheel	Weight(t)
M3G83F1010S	18000	2800	4500	6000	2800	4000	Paratactic tri- axle	53
M3G938F1210S	18000	2800	4500	6500	3000	4000	Paratactic tri- axle	58
M3G1142F1214G	18000	3000	4500	6500	3000	4200	Paratactic tri- axle	63

Specification and Technical Parameter

Parameter Model	Vibrating feeder	Impact crusher	Belt conveyor (down)	Belt conveyor (Up)	Belt conveyor	Vibrating screen	Capacity (t/h)	Power(kw)	Dynamo
M3G 83F1010S	GZD-850X300	PF1010	B500X7M	B650X15M	B650X 10M	3YA1548	30-275	95.5-115.5	adapting
M3G 938F1210S	GZD-960X3800	PF1210	B650X7M	B650X15M	B650X 10M	3YA1848	56-330	158.5-180.5	adapting
M3G 1142F1214G	GZD-1100X4200	PF1214	B650X8M	B800X16M	B800X 11M	3YA1860	65-586	196.5-232.5	adapting



Note :Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!