

Specification

Item	Compact 16	Compact 32
Rectified cast iron fixed table dimension	570x880 mm	
	350 x 1600 mm	350 x 3200 mm
Max. sawing carriage Ø355 mm(14")	standard	
Main saw blade Ø 205 mm (10")(CE)	Standard	
Main saw blade Ø 305 mm (12") (CE)	Optimal	
Main saw bore	Ø 30 mm (Ø 25.4 mm)	
Max. cutting height with blade at 90°	102 mm	
Max. cutting height with blade at 45 °	70 mm	
Main saw blade	5 HP (3,7 kw)	Standard
Motor	7.5 HP(5.5 kw)	Optimal
Main blade speed	4500 rpm	
Scoring saw blade Ø 120 mm	Standard	
Scoring saw blade bore	Ø 22 mm	
Scoring motor power	0.5 HP (0.37 kw)	Standard
	1 HP (0,75 kw)	Optimal
Scoring blade speed 8000 rpm	standard	
Cutting width 1000 mm	standard	-
Cutting width 1300 mm	-	Standard
Cutting width 1500 mm	-	Optimal
Cutting width adjustment	Manual	
Saw table extension 450 mm (CE)	optimal	Standard
Mite fence	-	standard
Blade tilting adjustment	Manual (0° ~ 45°)	
Main saw height adjustment	Manual	
Scorning saw height adjustment	Manual	
Scorning saw ± direction adjustment	Manual	
Blade tilting angle show	Mechanical display	
Overhead saw guard	Simple type	Standard
	Luxurious type	Optimal
Crosscut fence digital display	-	Optimal
Rip fence digital display	Optimal	
Rapid clamp	Optimal	
Tool frame	Non CE	Optimal
	CE	Standard
Dust collection system	Main Chanel 4", simple type 4", Lux. Type 4"	
Specifications subject to change without prior notice		

Technical specifications		Cutting depths			
Sliding table lengths 1600 mm (63")	Cutting lengths with cross-cut unit	Saw blade diameter	Ø250 mm (10")	Ø350 mm (12")	Ø 350 mm (14")
	1500 mm (59")	Cutting depth 90°	0~52 mm (0~2.04")	0~77 mm (0~3.03")	0~102 mm (0~4.01")
3200 mm (126")	3100 mm (122.05")	Cutting depth 45°	0~35 mm (0~1.37")	0~53 mm (0~2.04")	0~70 mm (0~2.75")

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!