

Horizontal Shaft Impact Crusher



Applications:

SECONDARY/TERTIARY CRUSHING:

- Mining
- Aggregate
- Demolition
- Industrial
- Construction
- Environmental

Advantages:

- Simple structure
- Simplified crushing process
- High-efficiency and energy conservation
- Cubic shaped desired products
- The discharge opening can be adjusted

PF Series-Two Cavities

Model	Specification (mm)	Feed Opening (mm)	Max. Feeding Size (mm)	Capacity (t/h)	Power (kw)	Weight (t) (Excluding Electric Motor)	Overall Dimensions (mm) (LxWxH)
PF-1007	F1000x700	400x730	300	35-50	37	9.5	2400x1560x2660
PF-1010	F1000x1050	400x1080	350	50-80	75	12.6	2440x2250x2630
PF-1210	F1250x1050	400x1080	350	70-120	110	14	2700x2340x2870
PF-1214	F1250x1400	400x1430	350	80-160	132	18.58	2700x2440x2900
PF-1315	F1300x1500	860x1520	500	160-260	200	24.2	2860x2800x3050

PF(V) Series –Three Cavities

Model	Specification (mm)	Feed Opening (mm)	Max. Feeding Size (mm)	Capacity (t/h)	Power (kw)	Weight (t) (Excluding Electric Motor)	Overall Dimensions (mm) (LxWxH)
PF-1010V	F1000x1050	400x1080	350	55-80	55-75	13.2	2400x2250x2660
PF-1210V	F1250x1050	400x1080	350	70-120	110-132	15.2	2696x2338x2890
PF-1214V	F1250x1050	400x1080	350	130-180	132-160	20	2690x2688x2890
PF-1310V	F1300x1050	400x1170	350	70-120	110-160	13.5	2780x2478x2855
PF-1315V	F1320x1050	860x1520	350	150-220	180-220	20.5	3096x3273x2667
PF-1515V	F1500x1500	850x1580	350	220-280	280-315	29.5	3550x2835x3270

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!