

▼ PF Impact Crusher

Dealing with the material with the side length below 500mm, not more than 250MPa anti-pressure strength, Impact crusher can be widely used in crushing the coarse, medium, and fine material(Eg. granite, limestone, concrete). During the process of operating, the rotor at high speed will be brought along by the electric motor. The material will be impacted by the Flat Hammer to be crushed, and then be countered to the liner for the second crushing, then be discharged through the discharge opening.



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

| Main Specification

Model	Specification (mm)	Feed Opening (mm)	Max.Feeding Size (mm)	Capacity (t/h)	Model of Motor	Power (kw)
PF-1007	φ1000×700	400×730	300	35-50	Y250M-6	37
PF-1010	φ1000×1050	400×1080	350	50-80	Y315S-6	75
PF-1210	φ1250×1050	400×1080	350	70-120	Y315L1-6	110
PF-1212	φ1250×1200	400×1250	350	70-140	Y315L2-6	132
PF-1214	φ1250×1400	400×1430	350	80-160	Y315L2-6	132
PF-1315	φ1300×1500	680×1520	350	90-220	Y2-355M2-6	200
PF-1320	φ1300×2000	680×1570	350	110-350	Y2-355M2-6	280

Model	Specification (mm)	Feed Opening (mm)	Max.Feeding Size (mm)	Capacity (t/h)	Model of Motor	Power (kw)
PFV-1007	φ1000×700	400×730	300	25-45	Y250M-6	55
PFV-1010	φ1000×1050	400×1080	350	35-60	Y315S-6	75
PFV-1210	φ1250×1050	400×1080	350	45-100	Y315L1-6	110
PFV-1214	φ1250×1400	400×1430	350	60-140	Y315L2-6	132
PFV-1315	φ1300×1500	565×1600	350	70-180	Y2-355M2-6	200
PFV-1320	φ1300×2000	496×2100	350	110-300	Y2-355M2-6	280